



# BEHTAM FARUSIA HR 70



## DESCRIPTION

Marine oils with very high safety margins especially formulated for the cylinder lubrication of slow speed 2 stroke crosshead Diesel engines.

## APPLICATIONS

Allowing for the most stringent conditions encountered in service, this full range of lubricants covers all operational needs.

- **BEHTAM FARUSIA HR 70** (SAE 50, BN 70): the most widely used lubricant for engines operating on intermediate or heavy fuels with a high sulphur level.

## PROPERTIES

This lubricant assures:

- minimal piston ring and liner wear
- maximum cleanliness
- reduced engine maintenance costs
- extended periods between overhauls.

# CHARACTERISTICS

CHARACTERISTICS	UNITS	BEHTAM FARUSIA HR 70
S.A.E. Grade		50
Density at 15 °C	kg/m <sup>3</sup>	940
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	20
Pour Point	°C	- 9
Flash Point (COC) ASTM D 92	°C	> 220
BN (ex TBN) ASTM D 2896	mgKOH/g	70

Characteristics of this chart are indicative typical values

## SPECIFICATION

**BEHTAM FARUSIA HR 70** meets the requirements of the major engine manufacturers.

## HANDLING, HEALTH AND SAFETY

**BEHTAM FARUSIA HR 70** range of lubricants consists of highly refined mineral oils with specific additives.

In normal conditions of use, these lubricants present no particular toxic hazard.

All lubricants, of any kind, should always be handled with great care, particularly avoiding any contact with the skin.

Prevent any risk of splashing, and keep away from combustible materials.

Store under cover and away from any risk of contamination.