

# RENOVATION PLUS SN 5W30



Very high performance lubricant using synthetics technology , intended for all Gasoline and Diesel car engines.

### APPLICATIONS

All Gasoline and Diesel engines

•Recommended for all Gasoline and Diesel engines in cars and light vans.

**Direct Injection & Turbocharger** 

· Particularly recommended to meet the enhanced requirements of direct injection Diesel engines with or without turbocharger.

The most severe journeys All times of year

· Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

Meets the requirements of

ACEA: C3-12 API: SN/CF

MB APPROVAL 229.3/229.5 VOLKSWAGEN 502.00/501.01 RENAULT RN0700/0710

### **CUSTOMER BENEFITS**

Very advanced Performance

• Outstanding engine protection particularly against wear.

Extension of engine's

lifetime

· Outstanding thermal stability and oxidation resistance, preventing any degradation even in very severe conditions.

Extension of out charge

intervals

• RENOVATION PLUS SN 5W30 has been engineered in order to comply with carmanufacturers requirements in terms of extended oil charge intervals.

## CHARACTERISTICS

	Method	Units	SAE Grade 5W-30
Density at 15°C	ASTM D1298	kg/m³	857
Viscosity at 40°C	ASTM D445	mm²/s	68.9
Viscosity at 100°C	ASTM 445	mm²/s	11.94
Viscosity index	ASTM D2270	-	170
Pour point	ASTM D97	°C	-39
Flash point	ASTM D92	°C	230
T.B.N.	ASTM D2896	mgKOH/g	10

The typical characteristics mentioned represent mean values

BEHTAM CO.











