



QUANTIC PLUS SN 5W30

Engine oil

KEY DATA

PETROL & DIESEL ENGINE OIL

SAE 5W-30

SYNTHETIC TECHNOLOGY

Meets the requirements of

- ACEA A1/B1,A5/B5,C2/C3
- API SN/CF
- MERCEDES-BENZ: MB-Approval 229.51, MB-Approval 229.31
- VOLKSWAGEN 502.00/505.01
- BMW LL-04
- GM DEXOS 2
- RENUALT RN0700/RN0710
- MB 226.5
- PORSCHE A40

APPLICATIONS

BEHTAM QUANTIC PLUS SN 5W30 is a synthetic technology engine oil that has been developed to cover the most stringent requirements of both gasoline and diesel passengers cars engines.

BEHTAM QUANTIC PLUS SN 5W30 complies with the latest ACEA and API international standards and meets the requirements of the most demanding automobile manufacturers.

This 5W30 grade lubricant is suitable for the most severe conditions of use (sports driving, repeated start-ups, city and motorway driving).

Its special formulation resists the most extreme variations in operating temperature. It is particularly well suited to modern multi-valve engines equipped with turbochargers and direct injection.

CUSTOMER BENEFITS

- **Antiwear protection:** this oil ensures optimum engine longevity with its antiwear properties that protect the engine's most sensitive parts.
- **Oxidation resistance:** this lubricant allows extra long drain intervals.
- **Engine protection, cleanliness and performance:** This oil contains detergent and dispersive additives that keep the engine clean and thus preserve its power.
- **Easier cold starts:** its excellent fluidity is perfectly adapted for cold starting in extreme weather conditions and ensures a good protection of mechanical parts at high temperature.
- **Fluidity:** Its exceptional fluidity reduces friction and therefore creates significant fuel savings and reduces CO2 emissions.

Fully synthetic oil for an **high and constant quality for the lubricant.**

CHARACTERISTICS*

Test	Unit	Test method	Result
Viscosity grade	-	SAE J300	5W-30
Viscosity at 40°C	mm ² /s	ASTM D445	69
Viscosity at 100°C	mm ² /s	ASTM 445	12
Flash point	°C	ASTM D92	234
Pour point	°C	ASTM D97	-39
Viscosity index	-	ASTM D2270	171
Phosphorus	ppm	ASTM D6595	800

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.