



QUANTIC SL 20W50

Engine oil

KEY DATA

	<u>Meets the requirements of</u>
	✓ API SL/CF
PETROL & DIESEL ENGINE OIL	✓ MB-Approval 229.1
SAE 20W-50	✓ VW 501.01 / 505.00

APPLICATIONS

BEHTAM QUANTIC SL 20W50 has been developed to cover the most stringent requirements of both gasoline and diesel engines* (passenger cars and light industrial vehicles).

BEHTAM QUANTIC SL 20W50 is particularly suited to turbocharged engines.

This engine oil is perfectly adapted to vehicles equipped with catalyts and using unleaded fuel or liquefied petroleum gas.

BEHTAM QUANTIC SL 20W50 can be used in all operating conditions (city traffic, road, motorways), whatever the season.

* The vehicle owner manual should be checked before using.

CUSTOMER BENEFITS

- **Manufacturers Standards:** BEHTAM QUANTIC SL 20W50 satisfies rigorous manufacturers standards (see above), while guaranteeing perfect and constant quality.
- **Resistance to Oxidation:** Thanks to very good antioxidant, antirust, antifoaming properties, BEHTAM QUANTIC SL 20W50 provides a specific resistance to oxidation.
- **Engine protection and cleanliness:** This oil ensures good engine cleanliness thanks to very high antiwear and anticorrosion properties.
- **Viscosity:** BEHTAM QUANTIC SL 20W50 has a high viscosity index and an excellent viscosity stability.

CHARACTERISTICS*

Test	Unit	Test method	Result
Viscosity grade	-	SAE J300	20W-50
Density at 15°C	kg/m ³	ASTM D4052	891
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	161.8
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	18.0
Viscosity index	-	ASTM D2270	124
Flashpoint	°C	ASTM D92	242
Pour point	°C	ASTM D97	-24

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.