


EQUIPER ZS



BEHTAM
RAVANKAR



Lubrication

High viscosity index anti-wear hydraulic oils.

APPLICATIONS

Hydraulic systems

- **EQUIPER ZS** range is recommended for all kind of hydraulic systems operating under high pressure (limit as indicated by the pump manufacturer) and high temperature.
- Lubricants especially suitable for hydraulic systems working under extreme temperature variations and equipment operating outside: easy start up at low temperature and regular operating in all seasons: civil engineering, agriculture, marine, transport and other industrial applications.

SPECIFICATIONS

Meets the requirements of

- AFNOR NF E 48-603 HV
- ISO 6743/4 HV
- DIN 51524 P3 HVLP
- VICKERS M-2950S, -I-286

ADVANTAGES

**Long equipment life time
High operating reliability**

- Very high viscosity index
- Good shear stability.
- Superior thermal stability avoiding the formation of sludge even at high temperature.
- Very good oxidation stability ensuring a long service life of the fluid.
- High protection against wear insuring maximum equipment life.
- Excellent hydrolytic stability avoiding filter blocking.
- Remarkable filterability even in the presence of water.
- Excellent protection against rust and corrosion.
- Good anti-foam and air release properties by using **silicon free** components.
- Very low pour point.
- Good demulsibility ensuring rapid water separation.

TYPICAL CHARACTERISTICS	METHODS	UNITS	EQUIPER ZS			
			32	46	68	100
Appearance	Internal	-	Clear liquid			
Density at 15°C	ASTM D 4052	kg/m ³	870	874	882	885
Viscosity at 40°C	ASTM D 445	mm ² /s	32	46	68	100
Viscosity at 100°C	ASTM D 445	mm ² /s	6.5	8.4	11.2	15.6
Viscosity index	ASTM D 2270	-	160	161	161	165
Cleveland flash point	ASTM D 92	°C	208	215	220	230
Pour point	ASTM D 97	°C	- 39	- 39	- 36	- 36
FZG (A/8, 3/90) - fail stage	DIN 51354	-	10	11	11	-
Filterability index (IF)	NF E 48-690	-	1.09	1.02	1.09	1.05
Shear resistance 250 cycles						
Viscosity loss @ 40°C	DIN 51382	%	3	5	8	-

Above characteristics are mean values given as an information.